.gearpump	R25/2,5 FL-Z-W-G3/4-R
acc. drawing	MZ 330000-1//1
complete assembled and tested	
suction connection	female thread G3/4
pressure connection	female thread G3/4

pump data:		
pumping medium		mineral oil
fluid temperature	in deg. C	<= 80
kin. viscosity	in mm²/s	33
oil flow approx.	in dm³/min	2,9
inlet pressure	in bar	0 (-0,4...+0,4)
outlet pressure	in bar	10
speed	in rpm	1450
sense of rotation (seen on shaft end)		cw
requested driving power	in kW	0,18 (10 bar, 33 mm²/s)
kind of shaft sealing		rubber radial shaft sealing
pressure relief valve		without
pump materials:		
casing		EN-GJL-250 (GG-25)
gearshafts		16MnCr5
elastomere		NBR
further data		
coating		1-component alkyd resin enamel RAL 6011 (reseda-green) thickness of the coat approx. 40 µm
internal pump preservation	(pump)	by test fluid
approx. net weight gearpump	in kg	3,9

A.m. product is not conform to
the ATEX rules.

Kontakt
Rickmeier GmbH
Langenholthauser Str. 20-22
D-58802 Balve
Postfach 13 40
D-58797 Balve

Telefon + 49 (0) 23 75 / 9 27-0
Telefax + 49 (0) 23 75 / 9 27-26
E-Mail kontakt@rickmeier.de
www.rickmeier.de

Banken
Commerzbank AG · Neuenrade
BLZ 458 400 26 Kto.: 2 911 444
SWIFT-Code COBADEFF 456
IBAN DE12 4584 0026 0291 1444 00

Volksbank im Märkischen Kreis eG
BLZ 447 615 34 Kto.: 13 505 200
SWIFT-Code GENODEM1NRD
IBAN DE93 4476 1534 0013 5052 00
Vereinigte Sparkasse im MK
BLZ 458 510 20 Kto.: 91 017 079

Sitz der Gesellschaft: Balve
Handelsregister Arnsberg HRB 4702
Geschäftsführer:
Christiane Schulz · Karl-Heinz Rietdorf
Mitglied im VDMA
Ust-IdNr.: DE 125583846